

Appl. No. 10/618,012
Amdt. Dated January 15, 2006
Reply to Office Action of November 15, 2005

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Claims 1. – 3. (Cancelled)

4. (Previously Presented) A liquid crystal display device comprising:
a pixel section having pixels arranged in a matrix which include active elements, and signal lines connected to columns of pixels, and wherein each pixel has a common electrode and a pixel electrode;

first control means for switching on the active elements for all the pixels in said pixel section when said liquid crystal display device is in a power-off state; and

second control means for setting, in the power-off state, all the signal lines to each have a potential equal or substantially equal to the potential of the common electrodes of the pixels; and

wherein said first control means is a vertical scanning system which sequentially switches on the active elements in units of rows when said liquid crystal display device is in a normal display mode, and which simultaneously switches on the active elements in the power-off state; and

wherein said second control means is a precharging scanning system which, in the normal display mode, supplies a precharging signal to the pixels in the row selected by said vertical scanning system before said a horizontal scanning system supplies the display signal to the pixels in the row selected by said vertical scanning system.

5. (Cancelled)

Appl. No. 10/618,012
Amdt. Dated January 15, 2006
Reply to Office Action of November 15, 2005

6. (Currently Amended) A liquid crystal display device comprising:
a pixel section having pixels arranged in a matrix which include active
elements, and signal lines connected to columns of pixels and wherein each pixel has
a common electrode and a pixel electrode; and
selecting means for selecting one of a first power-off mode and a second
power-off mode in accordance with the type of power-off state of said liquid crystal
display device,
wherein:
in the first power-off mode, in the power-off state, white level signals or black
level signals are written in all the pixels while the pixels in said pixel section are first
selected in a sequential manner in units of rows; and
in the second power-off mode, in the power-off state, the active elements for
all the pixels in said pixel section are switched on and all the signal lines are set to
each have a potential equal to the potential of common electrodes of the pixels A
~~liquid crystal display device according to claim 5, further comprising:~~

a power-off button; and
a power-supply battery,

wherein said selecting means selects the first power-off mode when the power-off state is caused by operating said power-off button, and selects the second power-off mode when the power-off state is caused by removing said power-supply battery.

Claim 7. (Cancelled)

8. (Previously Presented) A method for controlling a liquid crystal display device having pixels arranged in a matrix which include active elements, signal lines connected to columns of pixels, a power-off button, and a power-supply battery, and

Appl. No. 10/618,012
Amdt. Dated January 15, 2006
Reply to Office Action of November 15, 2005

wherein each pixel has a common electrode and a pixel electrode, said method comprising the steps of:

for a power-off state caused by operating the power-off button, writing white level signals or black level signal to all the pixels while first selecting the pixels in a sequential manner; and

for a power-off state caused by removing the power-supply battery, switching on the active elements for all the pixels, and setting all the signal lines to each have a potential equal to the potential of common electrodes of the pixels.

Claim 9. (Cancelled)

10. (Cancelled)